Load Balancing Computational Methods In A Short-code
Spread-spectrum Communications System

1.   A method of processing spread spectrum waveforms transmitted by a plurality of users
      of a spread spectrum system, comprising

      distributing among a plurality of logic units parallel tasks each for computing a portion
      of a matrix indicative of cross correlations among the waveforms transmitted by the
      users,

      executing with the plurality of logic units the distributed tasks.

2.   The method of claim 1, wherein the step of distributing comprises partitioning compu-
      tation of the cross-correlation matrix such that a computational load associated with a
      task distributed to one of said logic units is substantially equal to computational load
      associated with another task distributed to another logic unit.

3.   The method of claim 2, further comprising generating detection statistics correspond-
      ing to symbols transmitted by the users and encoded in the waveforms as a function of
      the cross correlation matrix.

4.   The method of claim 3, further comprising generating estimates of the symbols based
      on the detection statistics.

5.   The method of claim 3, further comprising the step of defining a metric associated with
      each partition in accord with the relation:

      $$B_i = A_i - A_{i-1}$$

      wherein

            A_i represents an area of a portion of the cross-correlation matrix corresponding
                to the i[th] partition, and

            i represents an index corresponding to the number of logic units.

6.   The method of claim 5, further comprising the step of representing the cross-correlation
      matrix as a composition of a rectangular component and a triangular component.

115

7. The method of claim 6, wherein each area A_i includes a first portion corresponding to the rectangular component and a second portion corresponding to the triangular component of the cross-correlation matrix.

8. The method of claim 7, wherein the step of partitioning the matrix includes selecting the matrix associated with the partitions to be substantially equal.

9. The method of claim 6, wherein the cross-correlation matrix is computed as a composition of a first component that represents correlations among time lags and code sequences associated with the waveforms transmitted by the users and a second component that represents correlations among multipath signal amplitudes associated with the waveforms transmitted by the users.

10. A method of processing spread spectrum waveforms transmitted by a plurality of users of a spread spectrum system, comprising

    partitioning computation of a matrix representing cross-correlations among the waveforms transmitted by the users in accord with a pre-defined metric,

    distributing among a plurality of logic units parallel tasks each corresponding to one of said partitions for computing a portion of the matrix, and

    executing with the plurality of logic units the distributed tasks.

11. The method of claim 10, further comprising assembling said computed portions to generate the cross-correlation matrix.

12. The method of claim 11, wherein the step of partitioning comprises defining the metric in accord with the relation:

    $$B_i = A_i - A_{i-1}$$

    wherein

    A_i represents an area of a portion of the cross-correlation matrix corresponding to the i^{th} partition, and

    i represents an index corresponding to the number of logic units.

116

13.   The method of claim 12, further comprising the step of generating detection statistics corresponding to symbols transmitted by the users and encoded in said waveforms as a function of the cross-correlation matrix.

14.   The method of claim 13, further comprising estimating the symbols based on said detection statistics.

15.   The method of claim 14, further comprising representing the cross-correlation matrix as a composition of a first component that represents correlations among time lags and code sequences associated with the waveforms transmitted by the users and a second component that represents correlations among multipath signal amplitudes associated with the waveforms transmitted by the users.

16.   The method of claim 15, further comprising the step of computing correlations among the code sequences associated with the respective users in accord with the relation:

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_{n=0}^{N-1} c_l^*[n] \cdot c_k[n-m]$$

wherein

   $\Gamma_{lk}[m]$ represents correlation between l and k user codes corresponding to a shift of m chips,

   $c_l^*[n]$ represents complex conjugate of the code sequences associated with the l^{th} user,

   $c_k[n-m]$ represents the code sequences associated with k^{th} user,

   N represents the length of the code, and

   N_l represent the number of non-zero length of the code.

17.   The method of claim 16, further comprising the step of computing the first component of the cross correlation matrix as a matrix component (herein referred to as C matrix) in accord with the relation:

$$C_{lkqq}[m'] = \sum_m g[mN_c + \tau] \cdot \Gamma_{lk}[m]$$

117

wherein

g is a pulse shape vector,

N_c is the number of samples per chip,

τ is a time lag, and

$\Gamma_{lk}[m]$ represents correlation between l and k user codes corresponding to a shift of m chips,

18. The method of claim 17, further comprising the step of computing the cross-correlation matrix (herein referred to as r matrix) in accord with the relation:

$$r_{lk}[m] = \sum_{q=1}^{L}\sum_{q'=1}^{L} \text{Re}\left\{ \hat{a}_{lq}^{*} \, a_{kq'} \cdot C_{lkqq'}[m] \right\} = \text{Re}\left\{ a_{l}^{H} \cdot C_{lk}[m] \cdot a_{k} \right\}$$

wherein

$\hat{a}_{lq}^{*}$ is an estimate of a_{lq}^{*}, which represents a complex conjugate of one multipath amplitude component of the l[th] user,

$a_{kq'}$ is one multipath amplitude component associated with the k[th] user, and

C denotes the aforesaid C matrix.

19. The method of claim 18, wherein the step of generating detection statistics comprises computing the detection statistics in accord with the relation:

$$y_l[m] = r_{ll}[0]b_l[m] + \sum_{k=1}^{K_r} r_{lk}[-1]b_k[m+1] + \sum_{k=1}^{K_r}[r_{lk}[0] - r_{ll}[0]\delta_{lk}]b_k[m] + \sum_{k=1}^{K_r} r_{lk}[1]b_k[m-1] + \eta_l[m]$$

wherein

$y_l[m]$ represents detection statistic for the mth symbol transmitted by the lth user,

$r_{ll}[0]b_l[m]$ represents a signal of interest, and

118

remaining terms of the relations represent Multiple Access Interference (MAI) and noise.

20.   The method of claim 19, wherein the step of generating symbol estimates comprises computing the estimates in accord with the relation:

$$\hat{b}_l[m] = sign\left\{ y_l[m] - \sum_{k=1}^{K_v} r_{lk}[-1]\hat{b}_k[m+1] - \sum_{k=1}^{K_v} [r_{lk}[0] - r_{ll}[0]\delta_{lk}]\hat{b}_k[m] - \sum_{k=1}^{K_v} r_{lk}[1]\hat{b}_k[m-1] \right\}$$

wherein

$\hat{b}_l[m]$ represents an estimate of the mth symbol transmitted by the lth user,

g is a pulse shape vector,

N_c is the number of samples per chip,

τ is a time lag, and

Γ represents the Γ matrix.